

BRIT® BITUMEN PRIMER

A specialized cold-applied single-component material for treating surfaces before arranging the roofing and water-proofing materials



Application Scope

An efficient material for preliminary treatment of insulation-subject surfaces before laying any roofing and water-proofing bitumen-based materials.

Advantages

- Reliable cohesion between materials and the base.
- Priming, dust removal, microcrack filling.
- Coatings and base longevity extension.



BRIT® PRIMER

Composition

Petroleum bitumen, organic solvents.
(STO 77310225.012-2017).

Packaging

Metal bucket, 20 l (18 kg).

Application Technology

- Remove dust, dirt, and grease from the surface.
- Stir the BRIT® primer thoroughly and apply it on a surface via a brush or a paddle roller.
- Let the primer dry up for 5-10 hours before subsequent works.
- If necessary, apply the primer again.

Characteristics

Parameter	BRIT® bitumen primer	Standard
Mass fraction of non-volatile substances, %, <i>at least</i>	40	GOST 31939
Heat resistance within 5 hours, °C, <i>at least</i>	80	GOST 2678
Water absorption within 24 hours, % by weight, <i>up to</i>	0,5	GOST 26589
3 degree drying-up time at t = 20±0.5 °C, h, <i>up to</i>	10	GOST 19007